





Backlighting

# JAWNLIGHT

Even illumination, endless possibilities—bring your design to life with Jawnligh



## Overview

- Luminous Block of Light
- Available in 5 white color temperatures at 12 Volts
- RGB available at 12 Volts
- Tunable available at 12 Volts
- Aesthetically pleasing glowing block of light
- Even illumination
- Custom Sizes Available

CODE	COLOR	DIMENSIONS <small>in inches</small>	LEAD WIRE	LED LOCATION	POWER CORD EXIT	DIMMING CONTROLS
JWN						
<div>30K = 3000 Kelvin 35K = 3500 Kelvin 41K = 4100 Kelvin 53K = 5300 Kelvin 63K = 6300 Kelvin TW = Tunable White RGB = Color Changing</div> <div>6SQ = 6" x 6" Square 6RD = 6" Round 12SQ = 12" Square 12RD = 12" Round X = Height X Width CS = Custom Shape</div> <div>LW05 = 5' Long LW10 = 10' Long</div> <div>LS1 = LED Strip on 1 long side LS2 = LED Strips on 2 long sides AS4 = LED Strips on all 4 sides</div> <div>SBB = Back corner same side as LED EDG = Edge side perpendicular to LED SSN = Notched corner same side as LED MID = Middle of LED side</div> <div>ND = Non-Dimmable 010 = 0-10V Dimming DMX = DMX Dimming (DMX Signal/Input by others)</div>						
<div>LED</div> <div>UL LISTED</div>						

# JAWNLIGHT

Static White

## Specifications



### Electrical

<b>Input Voltage</b>	12VDC
<b>Power Consumption</b>	5.0W/linear ft (Standard)
<b>Wire Size</b>	20 AWG 2 wire
<b>Wiring</b>	Each panel must have direct connection to power supply. Do not wire panels in series.
<b>Connector</b>	Bare wire (Standard)
<b>Certification</b>	UL/cUL
<b>CRI</b>	80

### Physical

<b>Color Temperature</b>	3000K, 3500K, 4100K, 5300K, 6300K
<b>Environment</b>	Dry Locations Only
<b>Mounting</b>	Wall mounted with Z-clips, Consult factory for other mounting options
<b>Minimum Size</b>	3" (75mm) x 3" (75mm)
<b>Maximum Size</b>	48" (1220mm) x 96" (2438mm)
<b>Weight</b>	5.85 lbs/sqft

## Diagrams



# JAWNLIGHT

Tunable White

## Specifications



### Electrical

<b>Input Voltage</b>	12VDC
<b>Power Consumption</b>	5.0W/linear ft (Standard)
<b>Wire Size</b>	20 AWG 2 wire
<b>Wiring</b>	Each panel must have direct connection to power supply. Do not wire panels in series.
<b>Connector</b>	Bare wire (Standard)
<b>Certification</b>	UL/cUL
<b>CRI</b>	80

### Physical

<b>Color Temperature</b>	3000K – 6500K
<b>Environment</b>	Dry Locations Only
<b>Mounting</b>	Wall mounted with Z-clips, Consult factory for other mounting options
<b>Minimum Size</b>	3" (75mm) x 3" (75mm)
<b>Maximum Size</b>	48" (1220mm) x 96" (2438mm)
<b>Weight</b>	5.85 lbs/sqft

## Diagrams



# JAWNLIGHT RGB

## Specifications

### Electrical

<b>Input Voltage</b>	12VDC
<b>Power Consumption</b>	5.0W/linear ft (Standard)
<b>Wire Size</b>	22 AWG 4 wire
<b>Wiring</b>	Each panel must have direct connection to power supply. Do not wire panels in series.
<b>Connector</b>	Bare wire, standard 5' (1500mm)
<b>Certification</b>	UL/cUL

### Physical

<b>Color Temperature</b>	RGB Color Changing
<b>Environment</b>	Dry Locations Only
<b>Mounting</b>	Wall mounted with Z-clips, Consult factory for other mounting options
<b>Minimum Size</b>	3" (75mm) x 3" (75mm)
<b>Maximum Size</b>	48" (1220mm) x 96" (2438mm)
<b>Weight</b>	5.85 lbs/sqft

## Diagrams

